



OCULAR AHUMADO 10446  
EN166 1 B 3 4, EN172 5-2,5



**Modelo**

**Scion**

**Referencia**

10445 (ocular claro) / 10446 (ocular ahumado)

### Características

Diseño moderno, robusto y compacto, permite el uso de gafas correctoras. Se adhiere al contorno de la cara por una pieza de goma suave que, por la parte inferior, hace la forma de un puente nasal muy cómodo.

Sello facial de TPE y ocular de grosor 2,4 mm.

Protección contra impactos, gotas, salpicaduras de líquidos y contra partículas grandes de polvo. Antivaho.

La goma se puede retirar.

Ocular de policarbonato, gran resistencia a la abrasión.

Amplia zona de visión y protección lateral.

Montura de PP y PC. Ajuste a la cabeza mediante una banda flexible de 1,8 cm de ancho, que se puede quitar girando la pieza plástica que une la banda a la gafa.

### Aplicaciones

- B-** Protección contra partículas a gran velocidad  
Impacto medio de energía (bala de 6 mm a 120 m/s).
- 3-** Protección contra gotas y salpicaduras de líquidos
- 4-** Contra partículas grandes de polvo.

### Standards

EN166 1B 3 4

#### CLASE ÓPTICA

Clase óptica 1 - Largos periodos de uso

#### MATERIALES

PP, PC, TPE

#### DIMENSIONES

Largo 21 cm zona más larga // Alto : Puente 3,5 cm, zona mas alta 7 cm

#### ESPESOR DEL OCULAR

2,4 mm // Curvatura: Hor. 8,1 m<sup>-1</sup> / Ver. 8,2 m<sup>-1</sup>

#### EMBALAJE

Bolsa plástica individual con instrucciones  
1 ud (unidad mínima de venta) // 120 uds (caja grande)





**SMOKE LENS 10446**  
EN166 1 B 3 4, EN172 5-2,5



### Model

Scion

### Reference

10445 (clear lens) / 10446 (smoke lens)

### Features

Polycarbonate, polypropylene and TPE goggle, 180° vision.

Protection against impacts and splashes of liquids.

Protection against large dust particles (4).

Anti-fog.

UV filter.

Prolonged use.

Sturdy, lightweight, and modern design.

Compatible with most prescription glasses.

### Applications

- B-** Protection against high speed particles  
Medium impact energy (6mm bullet at 120m / s).
- 3-** Protection against drops and splashes of liquids
- 4-** Against large dust particles.

### Standards

EN166 1B 3 4

#### OPTICAL CLASS

Optical class 1 - Prolonged use

#### MATERIALS

PP, PC, TPE

#### DIMENSIONS

Length 21 cm longest area // High : Nose bridge 3,5 cm, highest area 7 cm

#### THICKNESS OF THE LENS

2,4 mm // Curvatura: Hor. 8,1 m<sup>-1</sup> / Ver. 8,2 m<sup>-1</sup>

#### PACKAGING

Individual plastic bag with instructions  
1 pc (minimum unit of sale) // 120 pcs (big box)

