



Material: 90% PVC

Part n°	DETAILS	WIDTH (mm)	LENGTH (mm)	THICKNESS (mm)	M ² /ROLL	KG/M ²
ARSB12X12X15A	BLUE	1.220	12.000	15+/-0.5	16,64	5+/-0.3
ARSB12X12X15G	GRAY	1.220	12.000	15+/-0.5	16,64	5+/-0.3
ARSB12X12X15M	BROWN	1.220	12.000	15+/-0.5	16,64	5+/-0.3
ARSB12X12X15N	BLACK	1.220	12.000	15+/-0.5	16,64	5+/-0.3
ARSB12X12X15R	RED	1.220	12.000	15+/-0.5	16,64	5+/-0.3
ARSB12X12X15V	GREEN	1.220	12.000	15+/-0.5	16,64	5+/-0.3

Composition	PVC/PE/DOP/Color filler/Calcium
Manufacturing process	Extrusion and mechanical adhesion
Density	400 Kg/m ³
Temperature usage	-10°C/+65°C
Fire resistance	HG/T2015-91 B1 Grade
Benefits and applications	<ol style="list-style-type: none"> 1. UV resistant. Convenient for both outdoor and indoor solutions 2. It does not absorb humidity 3. Antislippery 4. Antidust
Base	No
Thread	0.8 mm